productinformation

tesa® 4434

Stencil Material for Sandblasting, Protection and Reinforcement

tesa® 4434 is a special masking tape with a strong, thick and resistant paper backing and has been developed for manual cutting. Due to the extreme resistance tesa® 4434 is mainly used as a protection material for grinding in workshops and base pads on tables during die-cutting in the shoe, leather and metal-working industry and further protection works.

Main Application

- Protection of car parts during professional lacquering work
- Perfect adhesion even on difficult surfaces
- Suitable for reinforcement of uppers
- Grinding and sandblasting

Technical Data

Backing material	flat paper	Elongation at break	6 %
Total thickness	670 μm	Tensile strength	180 N/cm
Type of adhesive	natural rubber	Temperature resistance	60 °C
Adhesion to steel	2.7 N/cm		

Properties

	Hand tearability	• •		Paint anchorage Sharp colour edge			•••	
	Plottability	•••				• •		
٠	Suitable for sandblasting	••••						
E۱	raluation across relevant tesa® assortment	: •••• very good	•	• good	• • medium	•	low	

Additional Information

The stencil material tesa® 4434 is used for sandblasting on tombstones and monuments, to cover serial plates during rust removal on steel vessels and for masking during sandblasting in bridge and machinery constructions.

Page 1 of 1 - as of 03/10/2018 -