

## tesa® 51571

### Double-sided non-woven tape

tesa® 51571 is a double-sided tape with a non-woven backing. It is used for permanent mounting of metal and plastic materials, e.g. aluminium, polystyrene, polypropylene, ABS. The very thick layer of adhesive bonds extremely well on uneven surfaces and has a very high initial bond.

### Main Application

tesa® 51571 is used for applications such as:  
Mounting of evaporator plates in the production of refrigerators

### Technical Data

▪ Backing material	non-woven	▪ Tensile strength	5 N/cm
▪ Color	translucent	▪ Type of liner	glassine
▪ Total thickness	160 µm	▪ Colour of liner	brown
▪ Type of adhesive	synthetic rubber	▪ Thickness of liner	70 µm
▪ Elongation at break	2.5 %	▪ Weight of liner	78 g/m <sup>2</sup>

### Adhesion to

▪ Steel (initial)	12.0 N/cm	▪ PS (initial)	12.4 N/cm
▪ ABS (initial)	11.8 N/cm	▪ PVC (initial)	12.0 N/cm
▪ Aluminium (initial)	13.0 N/cm	▪ Steel (after 14 days)	13.0 N/cm
▪ PC (initial)	13.4 N/cm	▪ PE (after 14 days)	8.5 N/cm
▪ PE (initial)	8.0 N/cm	▪ PP (after 14 days)	9.0 N/cm
▪ PET (initial)	10.6 N/cm	▪ PVC (after 14 days)	13.0 N/cm
▪ PP (initial)	9.0 N/cm		

### Properties

▪ Temperature resistance short term	80 °C	▪ Static shear resistance at 23°C	●●●●
▪ Temperature resistance long term	40 °C	▪ Static shear resistance at 40°C	●●●●
▪ Tack	●●●●	▪ Static shear resistance at 70°C	●●●●
▪ Ageing resistance (UV)	●●	▪ Fogging	●●●●
▪ Humidity resistance	●●●●		

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=51571>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.